



PILOT CLEAR LP25 - 1.5W

1.5 watt LED filament tubular pilot lamp

Application

Energy efficient LED lamp solutions

Design Specifications

- Clear glass diffuser, E14 base, 240V
- High efficiency LED filament and colour rendering, CRI>80
- Integral trailing edge non-dimmable LED driver
- 320° beam angle
- Colour temperature 3000K
- Suitable to replace equivalent incandescent tubular lamp or pilot lamps, double insulation



-
-
-
-
-
-
-
- WARM WHITE 3000K**

Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI	Beam Angle (°)
LP25F830E14	240	1.5	150	3000	80	320

Technical Specification

Model No.	Dimmable	Diameter (mm)	Length (mm)	Base Type
LP25F830E14	NO	25	58	E14

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions

LP25F

