



PORT MKIII SHP210 - 50W

IP66 LED area luminaire, IK10 rated

Application

A decorative and versatile exterior commercial solution

Design Specifications

- Stylish die-cast aluminium body, charcoal black finish
- Adjustable spigot (60mm OD) mounting, 0 - 90 degree.
- High efficiency SMD LED optics, CRI>70, CCT 5000K, standard Type V optical distribution.
- Integral constant current non-dimmable LED driver, pre-wired with 3 core rubber flex for easy termination
- Optional ELV PE cell configurations available to order, PEB shorting cap provided as standard.



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SHP210/50NDL2	240	50	8000	5000	70

Body Colour	Mass (kg)	Length (mm)	Width (mm)	Height (mm)
CHARCOAL BLACK	3.4	568	299	82

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

At SAL we are always thinking about how we can enhance our customers lighting experience & strongly believe **OUR SUCCESS IS MEASURED BY OUR CUSTOMERS SUCCESS.**



For more
information
please
scan me

