





RENMARK S9081D - 10W TC/WH

Dimmable IP44 10W LED downlight with selectable colour temperature

Application

Ideal for any residential, retail or commercial interior space

Design Specifications

- Premium aluminium body profile, IC-4 rated
- Stylish white body profile and WH trim with optional WH square, BK round or BK square quick connect trims to order
- High performance optical diffuser, beam 80°
- High efficiency SMD LED chips
- Remote constant current trailing edge dimmable flickerCONTROLLED LED driver, with flex and plug
- Selectable colour temperature 3000, 4000, 5700K



Dimmable - **YES** Dimmer Type - **Trailing edge, optional DALI**







Technical Specification


Model No.	Input Voltage (V/AC)		Power (W)	Lumens (lm)	ССТ (К)	Beam Angle (°)	Dimmable
S9081D10TC/WH	240		10	1000/1100/1050	3000/4000/5700	80	YES
S9081SQ/WH/P							
S9081RD/BK/P							
S9081SQ/BK/P							
Model No.	CRI	Body Colour		Cut Out (mm)	Diamete	er (mm)	Dim (mm)
S9081D10TC/WH	80	WHITE		92	11	4	66(H)
S9081SQ/WH/P		WHITE		92			114(L) x 114(W)
S9081RD/BK/P		BLACK		92	11	4	
S9081SQ/BK/P		BLACK		92			114(L) x 114(W)






Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions







THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER.





For related products please scan me





NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458