



RENMARK S9081R - 10W TC/WH

Dimmable IP44 10W LED downlight with selectable colour temperature

Application

Ideal for any retail, residential or commercial interior space

Design Specifications

- Premium aluminium body profile, IC-4 rated
- Stylish white body profile and WH trim with optional WH square, BK round or BK square quick connect trims to order
- High performance faceted reflector profile, beam 60°, UGR <19
- High efficiency SMD LED chips
- Remote constant current trailing edge dimmable flickerCONTROLLED LED driver, with flex and plug
- Selectable colour temperature 3000, 4000, 5700K



Performance

Dimmable - **YES**

Dimmer Type - **Trailing edge, optional DALI**

Technical Specification



Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)	Dimmable
S9081R10TC/WH	240	10	850/950/900	3000/4000/5700	60	YES
S9081SQ/WH/P						
S9081RD/BK/P						
S9081SQ/BK/P						

Model No.	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
S9081R10TC/WH	80	WHITE	92	114	66(H)
S9081SQ/WH/P		WHITE	92		114(L) x 114(W)
S9081RD/BK/P		BLACK	92	114	114(L) x 114(W)
S9081SQ/BK/P		BLACK	92		



Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



THE SFI SYSTEM ELIMINATES LED FLICKERING.

**SIMPLY
MATCH THE
ECO GEM SFI
DOWNLIGHT
WITH THIS
SDD400SFI
DIMMER.**



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

