



RENMARK S9081R10TC - 10W

10 watt LED downlight with selectable CCT, IP64

Application

Ideal for any retail, residential or commercial interior space

Design Specifications

- Premium aluminium body profile
- Stylish white body profile and WH trim with optional WH square, BK round or BK square quick connect plastic trims to order
- High performance faceted reflector profile, beam 60°, UGR <19
- Remote, premium trailing edge dimmable flickerCONTROLLED LED driver, with flex and plug
- Selectable CCT 3000K / 4000K / 5700K
- IC - 4 rated, double insulated



Performance

- Dimmable - **YES**
- Dimmer Type - **Trailing edge, 1-10V DALI / DSI**



Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)	Dimmable
S9081R10TC/WH	240	10	850/950/900	3000/4000/5700	60	YES
S9081SQ/WH/P						
S9081RD/BK/P						
S9081SQ/BK/P						

Model No.	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	IPART	REES
S9081R10TC/WH	90	WHITE	92	114	66(H)	N/A	N/A
S9081SQ/WH/P	90	WHITE	92		114(L) x 114(W)	N/A	N/A
S9081RD/BK/P	90	BLACK	92	114		N/A	N/A
S9081SQ/BK/P	90	BLACK	92		114(L) x 114(W)	N/A	N/A

Model No.	VEET
S9081R10TC/WH	N/A
S9081SQ/WH/P	N/A
S9081RD/BK/P	N/A
S9081SQ/BK/P	N/A

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".