



RENMARK S9082D20TC/DP - 14W/20W

14/20 watt LED downlight with selectable CCT and power, IP64

Application

Ideal for any retail, residential or commercial interior space

Design Specifications

- Premium aluminium body profile
- Stylish white body profile and WH trim with optional WH square, BK round or BK square quick connect plastic trims to order
- High performance mirror optical system, beam distribution 80°
- Remote, non-dimmable flickerCONTROLLED LED driver, with flex and plug
- Selectable CCT 3000K / 4000K / 5700K
- IC - 4 rated, double insulated

Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing Edge, 1-10V, DALI/DSI**



Technical Specification

Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Beam Angle (°)	Dimmable
S9082D20TC/DP	240	14/20	2100/2400/2300	3000/4000/5700	80	OPTIONAL
S9082SQ/WH/P						
S9082RD/BK/P						
S9082SQ/BK/P						

Model No.	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	IPART	REES
S9082D20TC/DP	90	WHITE	145	174	87(H)	N/A	N/A
S9082SQ/WH/P	90	WHITE	145		174(L) x 174(W)	N/A	N/A
S9082RD/BK/P	90	BLACK	145	174		N/A	N/A
S9082SQ/BK/P	90	BLACK	145		174(L) x 174(W)	N/A	N/A

Model No.	VEET
S9082D20TC/DP	N/A
S9082SQ/WH/P	N/A
S9082RD/BK/P	N/A
S9082SQ/BK/P	N/A

NOTE: lumens (lm) displayed are at MAXIMUM power

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".