



## SALRAY 5000 - SSIF5000

IP65 LED SOLAR floodlight - 5000 lumens

### Application

A sustainable floodlight solution for residential exterior spaces

### Design Specifications

- Robust black die-cast aluminium body, tempered glass diffuse and a versatile angled bracket for easy installation
- High efficiency LED optics, 5000 lumens, CRI 80, CCT 6500K, non-dimmable integral driver, beam distribution 120°
- Replaceable, lithium battery technology, with overcharge, over-discharge, load short circuit protection
- PIR and dusk to dawn control
- Detection range 110°, max 4-6m, installation height max 2.5m, hold time 25 sec, daylight threshold 20-30 lux, charge time 9 hours
- Optional remote sensor control - The default factory sensor MODE 1 setting, is dusk to dawn with 100% PIR sensor control. If other MODE settings are required, the optional remote controller is required which is sold separately, refer installation instructions for settings.





### Performance

- Dimmable - **NO**
- In Built Sensor - **YES**
- Sensor Type - **PIR DUSK TO DAWN**



## Technical Specification

Product	Model No.	Power (W)	Lumens (lm)	CCT (K)	CRI	Beam Angle (°)
 	SSIF5000	36	5000	6500	80	120
	SSIF/RC					

Body Colour	Dim (mm)	Mass (kg)
BLACK	322(L) x 386(H) x 46(D)	1.6
WHITE	85(L) x 40(W) x 5(D)	0.01

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Dimensions

