





SOL-ECO SL9725EM - 20/40W

MAINTAINED OR NON-MAINTAINED, LED emergency weatherproof batten, 20 or 40 watt models, with selectable CCT and power, IP65

Application

Multi-purpose, ceiling or suspension mount commercial or industrial applications

Design Specifications

- Vandal resistant design, robust PC body and UV stabilized polycarbonate diffuser, fitted polycarbonate
- Integral non-dimmable LED driver
- Compliant to AS/NZS2293 Emergency Lighting & Exit Signs, guaranteed minimum 90 minutes emergency mode function with LiFePO4 battery technology
- Installation types Surface mount (standard), if Suspended (two off, SSI1512 wire suspension kits are required).
- Emergency classification (20w) D25@C0, D50@C90, (40w) D25@C0, D50@C90





Performance

• Dimmable - NO



















Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Multiple Wattage	Lumens (lm)	CRI
	SL9725/20EM	240	20	10/20	2100/2300/2150	80
	SL9725/40EM	240	40	20/40	4100/4500/4200	80





CCT (K)	Beam Angle (°)	Body Colour	Dim (mm)	IPART	VEET	REES
3000/4000/5700	120	GREY	653(L) x 99(W) x 76(H)	N/A	N/A	N/A
3000/4000/5700	120	GREY	1253(L) x 99(W) x 76(H)			

Note: Lumens (lm) shown are displayed at FULL power

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





For more information please scan me





