



STARPAD SE7071TC - 15/100W

15-100 watt IP65 LED floodlight with integral selectable colour temperature

Application

A versatile floodlight solution for residential and commercial exterior spaces

Design Specifications

- Robust die-cast aluminium body, IK 07 rated
- Durable black, silver or white powder coated finish
- Textured tempered glass front cover
- High efficiency SMD LED chips, non-dimmable LED driver, CRI > 80, CCT selectable 3000 or 5000K
- High performance aluminium reflector, beam distribution 100 degree
- Nickel plated copper cable gland with 600 mm 3 core rubber flex (15-30 watt models), 800mm for (50-100 watt models)



Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
SE7071/15TC/WH	LED FLOOD LIGHT 15W IP65 3/5K WH	240	15	1300/1350	3000/5000	80
SE7071/15TC/SL	LED FLOOD LIGHT 15W IP65 3/5K SL	240	15	1300/1350	3000/5000	80
SE7071/15TC/BK	LED FLOOD LIGHT 15W IP65 3/5K BK	240	15	1300/1350	3000/5000	80
SE7071/30TC/WH	LED FLOOD LIGHT 30W IP65 3/5K WH	240	30	2550/2700	3000/5000	80
SE7071/30TC/SL	LED FLOOD LIGHT 30W IP65 3/5K SL	240	30	2550/2700	3000/5000	80
SE7071/30TC/BK	LED FLOOD LIGHT 30W IP65 3/5K BK	240	30	2550/2700	3000/5000	80
SE7071/50TC/WH	LED FLOOD LIGHT 50W IP65 3/5K WH	240	50	4250/4500	3000/5000	80
SE7071/50TC/SL	LED FLOOD LIGHT 50W IP65 3/5K SL	240	50	4250/4500	3000/5000	80
SE7071/50TC/BK	LED FLOOD LIGHT 50W IP65 3/5K BK	240	50	4250/4500	3000/5000	80
SE7071/100TC/WH	LED FLOOD LIGHT 100W IP65 3/5K WH	240	100	8500/9000	3000/5000	80
SE7071/100TC/SL	LED FLOOD LIGHT 100W IP65 3/5K SL	240	100	8500/9000	3000/5000	80
SE7071/100TC/BK	LED FLOOD LIGHT 100W IP65 3/5K BK	240	100	8500/9000	3000/5000	80

Model No.	Body Colour
SE7071/15TC/WH	WHITE
SE7071/15TC/SL	SILVER
SE7071/15TC/BK	BLACK
SE7071/30TC/WH	WHITE
SE7071/30TC/SL	SILVER
SE7071/30TC/BK	BLACK
SE7071/50TC/WH	WHITE
SE7071/50TC/SL	SILVER
SE7071/50TC/BK	BLACK
SE7071/100TC/WH	WHITE
SE7071/100TC/SL	SILVER
SE7071/100TC/BK	BLACK

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish.

Dimensions: LWH (mm) (15w) 153 x 153 x 33mm, (30w) 204 x 207 x 36mm, (50w) 246 x 261 x 39mm, (100w) 290 x 342 x 40mm

Product Images

