



TUBELINE STD25 TC - 9/36W

LED tube surface mount diffused linear batten 9 - 36 watt

Application

Conventional linear LED batten profile ideal for residential and commercial spaces

Design Specifications

- Durable metal body profile, white powder coat finish
- Large terminal block, easy installation
- High efficiency LED T8 tubes fitted, beam distribution 120°, CRI >80, with selectable CCT lamps included, 3000K/4000K/6000K
- Safety HRC fuse installed
- Emergency and sensor option available
- Wire guard (STG series) option available



Performance

- Dimmable - NO

Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	STD25/106TC	240	9	650/750/700	3000/4000/6000	80
	STD25/112TC	240	18	1800/2200/2000	3000/4000/6000	80
	STD25/206TC	240	18	1300/1500/1400	3000/4000/6000	80
	STD25/212TC	240	36	3600/4400/4000	3000/4000/6000	80

Beam Angle (°)	Dim (mm)	Body Colour	VEET
120	620(L) x 65(W) x 77(H)	WHITE	YES
120	1230(L) x 65(W) x 77(H)	WHITE	
120	620(L) x 110(W) x 77(H)	WHITE	
120	1230(L) x 110(W) x 77(H)	WHITE	

IMPORTANT, where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made,



otherwise equipment damage may occur.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

THE NEW ESS106 IS SMALL IN SIZE BUT BIG ON FEATURES.



For more
information
please
scan me

