





UFO SHB26MP - 80 / 200W

Super low profile, dimmable 1-10V LED highbay with selectable power, IP65.

Application

Versatile LED highbay ideal for commercial and industrial applications

Design Specifications

- Selectable power
- CCT 5000K, CRI >80 High efficiency LED optics, with an impressive 150lm/W optical performance at 150W or 200W
- Robust, black low profile die-cast aluminium body profile, IP65/IK08 protection
- High efficiency LED optics, 90° beam distribution, polycarbonate lens
- Integral dimmable 1-10V LED driver, complete with flex and plug for easy installation
- Optional plug and play corridorSTANDBY sensor

Performance

- Dimmable **YES**
- Dimmer Type 1-10V, optional SAL DALI signal converter
- In Built Sensor OPTIONAL
- Sensor Type MICROWAVE









Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Multiple Wattage	Lumens (lm)	Beam Angle (°)
	SHB26MP150NDL	240	150	80/120/150	12000/18000/22500	90
	SHB26MP200NDL	240	200	100/150/200	15000/22500/30000	90
	SHB23MP/CS					
	SHB25HES/RC					
	SHB26PMR150					
	SHB26PMR200					
	SHB26PPR150					
CALIFORNIA DAU Agrical convertion LAI-DAUDIN	LM-DALI010B					


CCT (K)	CRI	Body Colour	Diameter (mm)	Dim (mm)	Mass (kg)	IPART
5000	80	BLACK	320	137(H)	2.2	YES
5000	80	BLACK	360	137(H)	2.6	YES
		CORRIDOR SENSOR				
		REMOTE CONTROL				
		SILVER	500	236(H)		
		SILVER	573	264(H)		
		CLEAR PC	480	250(H)		
		DALI SIGNAL CONVERTER				


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".






Dimensions









S

.

272

70mm CUT OUT

For more information please scan me





NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

© Copyright SAL - All Rights Reserved