

GLSTRI (Dimmable)


LED Tri-CCT Dimmable GLS Globes

- Input voltage: 220-240V
- Diffuser: frosted plastic
- Housing: white plastic & aluminium
- Heatsink: PBT
- Tri-CCT (3000K / 4000K / 5000K) in one globe
- CCT switch on housing
- LED chips: 16pcs 2835
- CRI: >80
- Power factor: >0.5
- Ambient temperature: -20 to 40°C
- Suitable for dimming
- Suitable for 2-way switching
- Suitable for use with sensors



GLSTRI1D

GLSTRI2D



Tested & Recommended Dimmers:
 DIGINET, CLA, CLIPSAL, LEGRAND

*Please check with Licenced electrician for Min and Max dimmer load

*May be compatible with other untested dimmers



Part No	Description	Lumens			Watt	Dimensions	Box Weight	Box Size	Carton Qty
		3000K	4000K	5000K					
GLSTRI1D	GLOBE LED ES GLS DIMM TRI FR Wh	891LM	930LM	891LM	10W	Ø60X111mm	0.05kg	6x6x12cm	1/10/50
GLSTRI2D	GLOBE LED BC GLS DIMM TRI FR Wh	891LM	930LM	891LM	10W	Ø60X111mm	0.05kg	6x6x12cm	1/10/50