



Smart Jump Start Charger

Part No. **SJS05G2**

Generation 2

12V 500AMP

JUMP START MOST VEHICLES UP TO
3 Litre DIESEL (3000cc)
6 Litre PETROL (6000cc)

**JUMP START SAFE™
TECHNOLOGY**

Part No.	SJS05G2
12V 12,800mAh (47.36Whr) Lithium Polymer Battery	
POWER PACK SIZE	165mm X 79mm X40mm WEIGHT: 495G
JUMP START OUTPUT	12V DC 500Amp Peak / 300Amp Start
JUMPER LEADS	JUMP START SAFE Technology & AWG cable with MOSFET Reverse Current: >2 Amp Max. 18V DC Max. Voltage Difference Recognition, Short Circuit, Reverse Polarity, Overheat Temp Sensor, Power Pack Low Voltage, Anti Surge
SAFETY PROTECTION	Over discharge, Overcharge, Resettable Overload, Digital charging voltage and current recognition, Enclosed Jump Port Terminals
BATTERY CHARGERS	SAA Approved 240V AC / 15V DC 1Amp, 12V / 15V DC 800mA Car Charger
CHARGE CYCLES	2,000
AMBIENT TEMP	-20 to 60 DEG C
SELF DISCHARGE	10% to 15% over 12 months from full charge. With switch
OFF. DEVICE CHARGING	USB port 5V DC 2.1A with 4 in 1 USB cable IS8 compliant Multi Voltage Port 12V, 16V, 19V DC cable + 8 adaptors
LED FLASHLIGHT	3 Modes: (1)Full (2)S.O.S. (3)Emergency Flash
PACKAGING	Zip Carry Bag 10PCS per Carton

IMPORTANT NOTE: All SMART JUMP START chargers are designed as EMERGENCY jump starters and portable power supply which can charge most digital device batteries. It is capable of jump starting most vehicles with flat batteries. It is NOT a vehicle battery charger. It will NOT rectify existing starting system problems in vehicles. It is NOT to be used or attempt to be used as a permanent power supply for any vehicle.



Brochure updated on 22/07/2016

