



DIMMABLE SURFACE SERIES LED Surface Mounted Ceiling Lights

PRODUCT FEATURES

- ⊙ Input voltage: 240V AC 50/60Hz
- ⊙ Wattage: 12W & 18W
- ⊙ SMD2835 LED chips
- ⊙ Power factor: 0.9
- ⊙ Material: PC body, PMMA frosted diffuser
- ⊙ Double insulated
- ⊙ Designed in Australia
- ⊙ Dimmable with most trailing edge dimmers
- ⊙ Suitable for 3 wire sensor
- ⊙ Ambient temperature: -20 to 40°C
- ⊙ Large terminal holes for easy connection

LYNX ▶



RECOMMENDED DIMMERS:

| BRAND | CODE |
|-------------------------|-----------|
| CLA - trailing edge | LYNX |
| Clipsal - universal | 32E450UDM |
| Clipsal - trailing edge | 32E450TM |
| HPM - trailing edge | CAT400T |

TECHNICAL DATA

| CODE | DESCRIPTION | KELVIN | LUMENS | WATT (W) | CRI | DIAM | DEPTH | CARTON QTY |
|------------------|-----------------------------|--------|--------|----------|-----|--------|-------|------------|
| SURFACE2D | 12W WH FIXED RND 3000K DIMM | 3000K | 900LM | 12 | 82 | Ø178mm | 40mm | 1/20 |
| SURFACE3D | 18W WH FIXED RND 3000K DIMM | 3000K | 1450LM | 18 | 82 | Ø225mm | 40mm | 1/20 |
| SURFACE4D | 6W WH FIXED RND 5000K DIMM | 5000K | 480LM | 6 | 82 | Ø120mm | 40mm | 1/20 |
| SURFACE5D | 12W WH FIXED RND 5000K DIMM | 5000K | 960LM | 12 | 82 | Ø178mm | 40mm | 1/20 |
| SURFACE6D | 18W WH FIXED RND 5000K DIMM | 5000K | 1550LM | 18 | 82 | Ø225mm | 40mm | 1/20 |



Brochure updated on 29.11.2016

