




DIMMABLE SURFACE SERIES

LED Surface Mounted Ceiling Lights IP65



Product Features

- Input voltage: 240V AC 50/60Hz
- Wattage: 13W
- Material: aluminium
- Epistar COB LED chip
- Power factor: 0.9
- Ambient temp: -20 to 40°C
- Suitable for dimming
- Recommended Universal Trailing Edge and Leading Edge dimmers
- Not suitable for 2-way switching
- 3 year replacement warranty

Recommended dimmers: (2-8 pcs /dimmer)

- | | |
|-----------------------|----------------------|
| (1) CLA LYNX | (2) CLA-VELA |
| (3) Clipsal 32ELEDM | (4) Clipsal 31E2PUDM |
| (5) Clipsal 32E450UDM | (6) Clipsal 32E450LM |
| (7) HPM CAT250L | (8) HPM CAT250T |
| (9) HPM CAT400T | |

35,000 HRS	BEAM 40°	IP 65	3 YEAR WARRANTY	DIMMABLE
----------------------	--------------------	-----------------	---------------------------	-----------------

Technical data

CODE	DESCRIPTION	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	BEAM ANGLE	IP	DIMM	DIAM (mm)	DEPTH (mm)	CARTON QTY
SURFACE13	13W GLOSS WH LED S/M CEILING LIGHT 3000K	3000	800	13	>80	40°	IP65	YES	Ø105	146	1/12
SURFACE14	13W GLOSS WH LED S/M CEILING LIGHT 5000K	5000	900	13	>80	40°	IP65	YES	Ø105	146	1/12

Black fittings will be available in April 2017

UPDATED ON 23.01.2017