

Surface Mounted ceiling lights



PRODUCT FEATURES

- Input voltage: 240V AC 50-60Hz
- Wattage: 6W, 12W & 18W
- SMD2835 LED chips
- Life time: 30,000hrs
- PC body, PMMA lens
- Not suitable for dimming
- Operating temperature: -20 to 45°C
- IP20 for indoor use
- 5 year domestic & 3 year commercial warranty



DOUBLE INSULATED

CODE	DESCRIPTION	KELVIN	LUMENS (LM)	WATT (W)	CRI	BEAM (°)	DIAM. (mm)	DEPTH (mm)	CARTON QTY
SURFACE1	6W 30PCS LED WHT FIXED RND WW	3000K	450	6	82	160	Ø120	40	1/40
SURFACE2	12W 60PCS LED WHT FIXED RND WW	3000K	900	12	82	160	Ø178	40	1/20
SURFACE3	18W 92PCS LED WHT FIXED RND WW	3000K	1450	18	82	160	Ø225	40	1/20
SURFACE4	6W 30PCS LED WHT FIXED RND NW	5000K	480	6	82	160	Ø120	40	1/40
SURFACE5	12W 60PCS LED WHT FIXED RND NW	5000K	960	12	82	160	Ø178	40	1/20
SURFACE6	18W 92PCS LED WHT FIXED RND NW	5000K	1550	18	82	160	Ø225	40	1/20
SURFACE7	6W 30PCS LED WHT FIXED SQ WW	3000K	450	6	82	160	120	40	1/40
SURFACE8	12W 60PCS LED WHT FIXED SQ WW	3000K	900	12	82	160	178	40	1/20
SURFACE9	18W 92PCS LED WHT FIXED SQ WW	3000K	1450	18	82	160	225	40	1/20
SURFACE10	6W 30PCS LED WHT FIXED SQ NW	5000K	480	6	82	160	120	40	1/40
SURFACE11	12W 60PCS LED WHT FIXED SQ NW	5000K	960	12	82	160	178	40	1/20
SURFACE12	18W 92PCS LED WHT FIXED SQ NW	5000K	1550	18	82	160	225	40	1/20

UPDATED ON 28/09/2015

