

TABLET SERIES LED SLIM FLOOD LIGHTS



▲ TABLET1,2,6,7,8,9




▲ TABLET3,4,5

Product Features


- Input voltage: 240V AV 50/60Hz
- Material: aluminium
- SMD2835 LED chips
- Wattage: 10W-100W
- Life time: 30,000hrs
- CRI: 80
- Come with 300mm cable, **flex & plug not included**
- Recommended sensor: infrared sensor
- Ambient temp: **TABLET1-2:** -20 to 40°C;
TABLET3-9: -30 to 50°C
- Suitable for 2-way switching
- IP rating: IP65

Warranty


- 2 year replacement warranty




▲ TABLET1,3



▲ TABLET2,4,5,6



▲ TABLET7



▲ TABLET8,9

Technical Data

CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS		
		KELVIN (K)	LUMENS (LM)	WATT (W)	BEAM	WIDTH (mm)	DEPTH (mm)	CARTON QTY
TABLET1	10W MATT BLK SLIM LED FLOOD LIGHT 5000K	5000	700	10	120°	130	26	1/20
TABLET2	30W MATT BLK SLIM LED FLOOD LIGHT 5000K	5000	2100	30	120°	180	31	1/10
TABLET3	10W GLOSS WH SLIM LED FLOOD LIGHT 5000K	5000	800	10	100°	130	26	1/20
TABLET4	20W GLOSS WH SLIM LED FLOOD LIGHT 5000K	5000	1600	20	100°	180	31	1/16
TABLET5	30W GLOSS WH SLIM LED FLOOD LIGHT 5000K	5000	2400	30	100°	180	31	1/16
TABLET6	20W MATT BLK SLIM LED FLOOD LIGHT 5000K	5000	1600	20	100°	180	31	1/16
TABLET7	50W MATT BLK SLIM LED FLOOD LIGHT 5000K	5000	5000	50	100°	290	41.5	1/5
TABLET8	75W MATT BLK SLIM LED FLOOD LIGHT 5000K	5000	7500	75	100°	360	41.5	1/4
TABLET9	100W MATT BLK SLIM LED FLOOD LIGHT 5000K	5000	10000	100	100°	360	41.5	1/4

UPDATED ON 30.11.2016

