



JUNEE SL2116TC/DP - 9/30W

IP65 / IK10 LED ceiling mount oyster with corridor functions, selectable CCT and power

Application

A perfect choice for residential or apartments spaces

Design Specifications

- Selectable CCT 3000 / 4000 / 6000K and corridor functions
- Durable polycarbonate body profile with opal polycarbonate diffuser, colour white
- Rugged IK10 / IP65 construction, interior or covered exterior spaces
- High efficiency LED optics, 120° beam distribution, CRI > 80
- Integral, dimmable flickerCONTROLLED gear with selectable power models 9/13W, 17/24W and 21/30W
- Double insulated









Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing Edge refer model**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MV CORRIDOR**





Technical Specification

| Product | Model No. | Input Voltage (V/AC) | Multiple Wattage | Lumens (lm) | CCT (K) | CRI |
|--|------------------|----------------------|------------------|----------------|----------------|-----|
|  | SL2116/20TC/DP | 240 | 9/13 | 1400/1500/1450 | 3000/4000/5700 | 80 |
|  | SL2116/30TC/DP | 240 | 17/24 | 2750/2800/2700 | 3000/4000/5700 | 80 |
|  | SL2116/40TC/DP | 240 | 21/30 | 3150/3450/3300 | 3000/4000/5700 | 80 |
|  | SL2116/20TC/DP/C | 240 | 9/13 | 1400/1500/1450 | 3000/4000/5700 | 80 |
|  | SL2116/30TC/DP/C | 240 | 17/24 | 2750/2800/2700 | 3000/4000/5700 | 80 |
|  | SL2116/40TC/DP/C | 240 | 21/30 | 3150/3450/3300 | 3000/4000/5700 | 80 |

| Dimmable | Beam Angle (°) | Body Colour | Diameter (mm) | Dim (mm) | Mass (kg) |
|----------|----------------|-------------|---------------|----------|-----------|
| YES | 120 | WHITE | 200 | 59(H) | 0.47 |
| YES | 120 | WHITE | 280 | 59(H) | 0.7 |
| YES | 120 | WHITE | 360 | 59(H) | 1.13 |
| NO | 120 | WHITE | 200 | 59(H) | 0.48 |
| NO | 120 | WHITE | 280 | 59(H) | 0.71 |
| NO | 120 | WHITE | 360 | 59(H) | 1.14 |

NOTE: Lumens displayed (lm) are at the maximum power selection

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions

