



Image for illustration purposes only.

**All LED strip must be installed on an aluminium heat dissipating surface**



## Warm White LED Strip Kits

- Viper LED flexible strip light
- Dimmable using Havit LED controllers
- Peel and stick backing for initial placement
- Cuttable every 50mm for 60 LED per mtr
- Beam angle 120 degrees
- All LED strip must be installed using anti-static measures and on an aluminium heat dissipating surface for warranty purposes (HV9705-1003 or HV9705-1603)

**IP20 (4.8w,7.7w, 9.6w)**



## Cool White LED Strip Kits



Image for illustration purposes only.

**All LED strip must be installed on an aluminium heat dissipating surface**



- Viper LED flexible strip light kits
- Dimmable using Havit LED controllers
- Peel and stick backing for initial placement
- Beam angle 120 degrees
- All LED strip must be installed using anti-static measures and on an aluminium heat dissipating surface for warranty purposes (HV9705-1003 or HV9705-1603)



**IP20 (4.8w,7.7w, 9.6w)**



All low voltage products that specify LED or are supplied with a 12v DC LED globe must be used with a suitable LED driver, refer to pages (185 - 206)  
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to pages (257 - 258)



# VIPER Kits

## Warm White LED Strip Lighting Kits

IMAGE	LENGTH	PART NUMBER	SMD	IP RATING	COLOUR TEMP	OUTPUT	POWER	DIMMABLE
	2 mtr	VPR9733IP54-60-2M	3528	IP54 WATER RESISTANT	Warm white, 3000k	780lm 120 LED	12v DC 4.8w per 1m	Using Havit LED Controllers
	5 mtr	VPR9733IP54-60-5M	3528	IP54 WATER RESISTANT	Warm white, 3000k	1950lm 300 LED	12v DC 4.8w per 1m	Using Havit LED Controllers

# VIPER Kits

## Cool White LED Strip Lighting Kits

IMAGE	LENGTH	PART NUMBER	SMD	IP RATING	COLOUR TEMP	OUTPUT	POWER	DIMMABLE
	2 mtr	VPR9734IP54-60-2M	3528	IP54 WATER RESISTANT	Cool white, 5500k	860lm 120 LED	12v DC 4.8w per 1m	Using Havit LED Controllers
	5 mtr	VPR9734IP54-60-5M	3528	IP54 WATER RESISTANT	Cool white, 5500k	2150lm 300 LED	12v DC 4.8w per 1m	Using Havit LED Controllers

All low voltage products that specify LED or are supplied with a 12v DC LED globe must be used with a suitable LED driver, refer to pages (185 - 206)  
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to pages (257 - 258)