

TUBELINE DIFFUSE STD

Conventional LED diffuse battens 9 - 36 watt

Application

Conventional LED interior battens ideal for residential and commercial service spaces

Design Specifications

- Pressed steel base with PVC body
- Large terminal block, easy installation
- Quality white powder coat finish
- High efficiency LED T8 tubes fitted, beam distribution 120 degree, CRI >80, 3000, 4000, 6000K
- Safety fuse installed, emergency compliant to AS/NZS2293 and sensor models available
- Dimensions: LWH: (9W) 625 x 65 x 77mm, (18W) 1225 x 65 x 77mm, (2x9w) 625 x 110 x 77mm, (2x18W) 1225 x 110 x 77mm

Performance

In Built Sensor - **OPTIONAL**
Sensor Type - **MICRO**



Technical Specification

Model No.	Description	Input (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
STD/106 CW	LED DIFF. BAT. 9W 600mm 4K	240	9	850	4000	80
STD/106 DL	LED DIFF. BAT. 9W 600mm 5K	240	9	900	5000	80
STD/112 CW	LED DIFF. BAT. 18W 1200mm 4K	240	18	1600	4000	80
STD/112 DL	LED DIFF. BAT. 18W 1200mm 6K	240	18	1700	6000	80
STD/206 CW	LED DIFF. BAT. 2 X 9W 600mm 4K	240	18	1700	4000	80
STD/206EM2500	LED EMERG. BATTEN 2 X 9W 4K	240	18	n/a	4000	80
STD/212 CW	LED DIFF. BAT. TWIN 1200mm 4K	240	36	3200	4000	80
STD/212 DL	LED DIFF. BAT. TWIN 1200mm 6K	240	36	3400	6000	80
STD/212EM2500	LED EMERG. DIFF. BAT. TWIN 4K	240	36	n/a	4000	80



Model No.	Body Colour
STD/106 CW	WHITE
STD/106 DL	WHITE
STD/112 CW	WHITE
STD/112 DL	WHITE
STD/206 CW	WHITE
STD/206EM2500	WHITE
STD/212 CW	WHITE
STD/212 DL	WHITE
STD/212EM2500	WHITE