

Santorini

4-in-1 thermal bathroom unit

- 2000W PTC heater that efficiently heats the air
- 45W ball bearing motor for excellent reliability
- High-velocity 535m³ per hour air extraction
- Fan function for warm weather cooling
- Quality integrated tri-CCT (non-dimmable) LED panel provides efficient illumination
- Ideal for medium to large bathrooms
- 3-year in-home warranty for peace of mind
- Includes integrated draught stopper, wall switches, 1.5m duct and grill outlet



ORDERING INFORMATION

Order code	14835
Description	2000W PTC high velocity bathroom heater & exhaust w/LED panel - Black - tri-cct
Item Code	SANTORINI/B

EFFICIENCIES

Total System Efficiency 72 lm/W

The performance of each component of a luminaire is demonstrated through its efficiencies, which together determine the total system efficiency of the product. The output of the LED chip is first multiplied by the optical and thermal efficiencies to calculate the Luminaire efficiency. However, this calculation does not consider the driver efficiency. To determine the overall efficiency of the system, the Luminaire efficiency must be multiplied by the driver efficiency, which accounts for all losses in the system.

MECHANICAL

IP Rating	IPx2
Fitting Colour	Black
Installation Type	Recessed

ELECTRICAL

Input Frequency	50 Hz
Input voltage	230Vac

In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%

LAMP

Colour Rendering Index (CRI)	>80
CCT Configuration	TRI-CCT

COLOUR TEMPERATURE

20 Watts

Warm White (3000 K)	1300 lm
Cool White (4000 K)	1450 lm
DayLight (5000 K)	1350 lm

AIR MOVEMENT

Outlet	125 mm
Noise level	52 dB
Motor Wattage	45 W
Motor Type	Ball bearing

HEAT

Heater Type	PTC heater
--------------------	------------

COMPLIANCE

Standards	AS/NZS 60335.1 AS/NZS 60335.2.30 AS/NZS 60335.2.80 AS/NZS 60598.1 AS/NZS 60598.2.2 AS CISPR 15
------------------	---

WARRANTY

Domestic Use Warranty	3 Onsite (Total 3 Years)
-----------------------	--------------------------

DIMENSIONS

Product Height	125 mm
Product Length	610 mm
Product Width	339 mm
Minimum Ceiling Depth	220 mm
Cutout	310x580 mm

LINE DRAWINGS

SANTORINI/WH
SANTORINI/B

