

Vanuatu

4 blade 40W DC ceiling fan

- Quiet and efficient 40W DC motor
- ABS construction ideal for coastal conditions
- Includes 3 speed DC wall control
- Ideal for outdoor undercover patio areas
- Reversible for summer and winter use
- Quick connect wiring for ease of installation
- Easy blade assembly
- 15W dimmable tri-colour LED
- Switchable colour temperature between 3000K, 4000K and 5000K
- Lumen output of up to 1145lm

ORDERING INFORMATION

| | |
|--------------------|---|
| Order code | 15222 |
| Description | 48 inch (1220mm) 4 blade 40W DC ceiling fan W/LED Light white |
| Item Code | VANUATU/48/LT/WH |

MECHANICAL

| | |
|-----------------------|-------------|
| IP Rating | IP20 |
| Fitting Colour | Satin White |
| Body Material | ABS |

ELECTRICAL

| | |
|---------------------------|--------------|
| Working Temp Range | -10 to 40 °C |
| Input Frequency | 50 Hz |
| Input voltage | 230Vac |

In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%

AIR MOVEMENT

| | |
|-----------------------|--|
| Motor Wattage | 40 W |
| Motor Type | DC |
| No. Speeds | 3 |
| Control | Wall control |
| Ceiling Rake | 15 ° |
| Ceiling Drop | 330 mm |
| Blade Material | ABS |
| Fan Size | 1220mm (48inch) |
| Fan Speed 1 | 40 W, 206 rpm, 11200 m ³ /h |



| | |
|--------------------|---------------------------------------|
| Fan Speed 2 | 20 W, 165 rpm, 9400 m ³ /h |
| Fan Speed 3 | 5 W, 100 rpm, 5000 m ³ /h |

COMPLIANCE

| | |
|------------------|--|
| Standards | AS/NZS 60335.1 AS/NZS 60335.2.80 AS/NZS 60598.1 AS/NZS 60598.2.2 AS CISPR 15 |
|------------------|--|

LINE DRAWINGS

VANUATU/48/LT/WH

