

## Vanuatu

4 blade 40W DC ceiling fan

- Quiet and efficient 40W DC motor
- ABS construction ideal for coastal conditions
- Includes 3 speed DC wall control
- Ideal for outdoor undercover patio areas
- Reversible for summer and winter use
- Quick connect wiring for ease of installation
- Easy blade assembly
- 15W dimmable tri-colour LED
- Switchable colour temperature between 3000K, 4000K and 5000K
- Lumen output of up to 1145lm

### ORDERING INFORMATION

<b>Order code</b>	15224
<b>Description</b>	52 inch (1320mm) 4 blade 40W DC ceiling fan W/LED Light white
<b>Item Code</b>	VANUATU/52/LT/WH

### MECHANICAL

<b>IP Rating</b>	IP20
<b>Fitting Colour</b>	Satin White
<b>Body Material</b>	ABS

### ELECTRICAL

<b>Working Temp Range</b>	-10 to 40 °C
<b>Input Frequency</b>	50 Hz
<b>Input voltage</b>	230Vac

In Australia the Input voltage is defined as 230Vac -6%/+10%. This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%

### AIR MOVEMENT

<b>Motor Wattage</b>	40 W
<b>Motor Type</b>	DC
<b>No. Speeds</b>	3
<b>Control</b>	Wall control
<b>Ceiling Rake</b>	15 °
<b>Ceiling Drop</b>	330 mm
<b>Blade Material</b>	ABS
<b>Fan Size</b>	1320mm (52inch)
<b>Fan Speed 1</b>	40 W, 186 rpm, 11100 m <sup>3</sup> /h



<b>Fan Speed 2</b>	20 W, 145 rpm, 8800 m <sup>3</sup> /h
<b>Fan Speed 3</b>	5 W, 90 rpm, 4600 m <sup>3</sup> /h

### COMPLIANCE

<b>Standards</b>	AS/NZS 60335.1 AS/NZS 60335.2.80 AS/NZS 60598.1 AS/NZS 60598.2.2 AS CISPR 15
------------------	--

### LINE DRAWINGS

#### VANUATU/52/LT/WH

