



### PICTOGRAMS INCLUDED



### BLACK AVAILABLE



240V 50Hz	5W TOTAL WATTAGE	2W MAINTD LAMP	1W NON-MTD LAMP	SMD LED			CRI >83	Ta 40°C	C0: E5.0 C90: E2.0
--------------	------------------------	----------------------	-----------------------	---------	--	--	------------	------------	-----------------------

Blade Exit Sign is a general purpose, double or single sided interior recessed mounted exit sign for use at doorway, stairways and corridors and intersection on an emergency escape route. The LED exit sign with integral emergency 2 hour battery pack permits self-powered operation during power outage.

### FEATURES

- 50,000 Hour average life rated LED modules
- Recessed & Surface mount options
- Injection moulded polycarbonate housing and acrylic diffuser with pictogram legends
- Viewing distance 24M
- High density storage LiCoO<sub>2</sub> batteries
- Diffuser & pictogram inserts included
- IP20 rating
- Additional 1W Non-Maintained downlight during mains power outage
- Emergency driver fully tested & compliant with SAA
- 2 Hour duration period
- TA40 - maximum thermal ambient operating temperature
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous

### APPLICATIONS

A stylish Exit sign ideal for emergency lighting application where aesthetics are everything including commercial office areas, hotels, shopping, apartments & hospitals.

### CLASSIFICATION & SPACING DISTANCE

		Mounting Height in Metres									
Plane	Class	2.1	2.4	2.7	3.0	3.6	4.0	4.5	5.0	6.0	
C0	E5.0	6.6	7.2	7.4	7.8	8.0	8.2	8.4	8.4	8.2	
C90	E2.0	5.2	5.2	5.4	5.0	4.6	4.8	4.0	-	-	

MODEL NO.	MOUNT TYPE	MAINTAINED LAMP WATTAGE (W)	NON-MAINTAINED LAMP WATTAGE (W)	FITTING COLOUR	
19878/..	RECESSED	2	1	/05-WHITE	/06-BLACK
19880/..	SURFACE	2	1	/05-WHITE	/06-BLACK
19893/..	SURFACE MOUNT BOX ONLY			/05-WHITE	/06-BLACK

