



PICTOGRAMS INCLUDED



BLACK AVAILABLE



240V 50Hz	5W TOTAL WATTAGE	2W MAINTD LAMP	1W NON-MTD LAMP				CRI >80	Ta 40°C	C0: E2.0 C90: E1.6	C0: E12.5 C90: E12.5
			19876		19876				19874	19876

One-Box Exit Sign is a general purpose, double or single sided interior ceiling or wall mounted sign for use at doorway, stairways and corridors and intersection on an emergency escape route. The LED exit sign with integral emergency 2 hour battery pack permits self-powered operation during power outage.

FEATURES

- 50,000 Hour average life rated LED modules
- Surface-mount Ceiling or Wall
- Injection moulded polycarbonate housing and acrylic diffuser with pictogram legends
- Viewing distance 24M
- High density storage LiCoO₂ batteries
- Diffuser & pictogram inserts included
- IP20 rating
- Additional 1W Non-Maintained downlight during mains power outage (19876 only)
- Emergency driver fully tested & compliant with SAA
- 2 Hour duration period
- TA40 - maximum thermal ambient operating temperature
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous

APPLICATIONS

A general purpose Exit sign suitable for use at doorways, stairways, corridors and intersections on an emergency escape route.

CLASSIFICATION & SPACING DISTANCE

Model	Mounting Height in Metres										
	Plane	Class	2.1	2.4	2.7	3.0	3.6	4.0	4.5	5.0	6.0
19874	C0	E2.0	5.2	5.2	5.4	5.2	5.0	4.6	4.8	4.0	-
	C90	E1.6	4.8	4.8	4.8	4.4	4.2	3.8	-	-	-
19876	C0	E12.5	8.0	8.8	9.4	10.0	10.4	11.0	11.4	12.0	12.4
	C90	E12.5	8.0	8.8	9.4	10.0	10.4	11.0	11.4	12.0	12.4

MODEL NO.	MAINTAINED LAMP WATTAGE (W)	NON-MAINTAINED LAMP WATTAGE (W)	FITTING COLOUR	
19874/..	2	-	/05-WHITE	/06-BLACK
19876/..	2	1	/05-WHITE	/06-BLACK

