

PATHFINDER

3W LED EMERGENCY LUMINAIRE

SURFACE MOUNT



RECESSED

BLACK ALSO AVAILABLE ON REQUEST



240V 50Hz	5W TOTAL WATTAGE	3W NON-MTD LAMP	SMD LED		CRI >80	Ta 40°C	D40	70-130mm
--------------	------------------------	-----------------------	---------	--	------------	------------	-----	----------

Pathfinder Emergency downlight 3W LED is a general purpose, versatile non-maintained LED emergency luminaire with D40/D40 classification, compliant to AS/NZS2293 for interior use wherever emergency lighting is required. The LED luminaire with emergency 2 hour battery pack permits self-powered operation during power outage.

FEATURES

- Energy efficient high output 3 watt LED
- 2-Pin flex & plug included
- Recessed or surface ceiling mount options available
- Injection moulded polycarbonate housing
- Removeable large trim ring included
- D40/D40 classification
- High density storage LiCoO₂ batteries
- IP20 rating
- Emergency driver fully tested & compliant with SAA
- 2 Hour duration period
- TA40 - maximum thermal ambient operating temperature
- Charger type: Trickle
- Charger time: 16 Hours
- Charger operation: Continuous
- Cutout: 70 to 130mm

APPLICATIONS

Commercial and interior applications, coastal environment, apartments, shopping centres, hospitality, prisons and hospitals.

CLASSIFICATION & SPACING DISTANCE

		Mounting Height in Metres								
Plane	Class	2.1	2.4	2.7	3.0	3.6	4.0	4.5	5.0	6.0
C0	D40	16.7	17.4	18.0	18.6	19.6	20.1	20.8	21.3	22.1
C90	D40	16.7	17.4	18.0	18.6	19.6	20.1	20.8	21.3	22.1

MODEL NO.	MOUNT TYPE	NON-MAINTAINED LAMP WATTAGE (W)	FITTING COLOUR	
19882/..	RECESSED	3	/05-WHITE	/06-BLACK
19886/..	SURFACE	3	/05-WHITE	/06-BLACK
19895/..	SURFACE MOUNT BOX ONLY		/05-WHITE	/06-BLACK

