

UMBRA II


HIGH LUMEN SMD LED DOWNLIGHT

LED Performance
Solid State Lighting Luminaire



240V	11W rated 14W w/driver		3000K WARM WHITE	4200K COOL WHITE				100° BEAM ANGLE	CRI >82	POWER FACTOR 0.95	CONSTANT CURRENT 350mA		
			17835	17837									

RECOMMENDED INSTALL CLEARANCES:



The ideal downlight for replacing existing fluorescent downlights, by providing a wide angled diffused beam.

- 50 x SMD 2835 LED Chips provide high quality light output
- SAA approved dimmable LED driver with
- 0.7m flex & plug.
- Long lasting up to 30,000 hours, (limited by driver).
- 3 Year Warranty.

* Complies with IEC 60598-1: 2008 and IEC 60598-2-2: 2011 (50°C ambient).

Recessed luminaires suitable for covering in the ceiling void with thermal insulating material (without causing overheating to the luminaire) are marked with this variation of the F mark symbol.



Code:	17835/..			
05 WHITE	11 WATTS	780 LUMENS	56 lm/W	
13 BRUSHED NICKEL	11 WATTS	780 LUMENS	56 lm/W	
Code:	17837/..			
05 WHITE	11 WATTS	800 LUMENS	57 lm/W	
13 BRUSHED NICKEL	11 WATTS	800 LUMENS	57 lm/W	

