

XL-LED Performance LED Candle Lamps



WARM 1000K
2700K WARM
COOL 7000K

ENERGY SAVING 50%
LAMP LIFE 35,000
LAMP LIFE 30,000
240V

3W 175 LUMENS
3.8W 220 LUMENS

120 (mm) | 36 | SES Base
 122 (mm) | 37.5 | ES Base
 114.5 (mm) | 37.5 | SBC Base
 121 (mm) | 37.5 | BC Base

PRODUCT SPECIFICATIONS

	ELECTRICAL	
	Clear	Opal
Supply Voltage	240V AC	240V AC
Supply Frequency	50-60Hz	50-60Hz
Supply Current	0.02A	0.35A-0.55A
Power Factor	0.9	0.5-0.6
Lamp Power	3W	3.8W

	MATERIALS	
	Heatsink	Aluminium
Body	Aluminium, thermoplastic	Aluminium
Lens / Diffuser	Polycarbonate	Glass

	THERMAL	
	Ambient Temperature Rating	-20°C to 45°C
Maximum Surface Temp	<55°C	<60°C

	OPTICAL / PHOTOMETRIC	
	Luminous Flux	175 lumens
CRI	80	70
Colour Temperature	2700K	3000K
Beam Angle	120°	160°

	WEIGHT / LIFE	
	Lamp	60g
LED Lamp Life	35,000HR	30,000HR

PRODUCT FEATURES

- LED candle lamp
- Aluminium body with thermoplastic base
- Clear / opal diffuser

* Compared to a standard 25W incandescent candle lamp



REFERENCE	Base	CODE
Clear		
LEDCAN3WSES27K	SES E14	26873
LEDCAN3WES27K	ES E27	27025
LEDCAN3WSBC27K	SBC B15	27023
LEDCAN3WBC27K	BC B22	27024
Opal		
LEDCANP3WSES3K	SES E14	27111
LEDCANP3WES3K	ES E27	27112
LEDCANP3WSBC3K	SBC B15	27109
LEDCANP3WBC3K	BC B22	27110

XL-LED PERFORMANCE

Lamps