



XL-LED Performance Small Circular Ceiling Lights



XLLED116S / XLLED116SD



PRODUCT FEATURES

XL-LED Performance 240V Circular LED Ceiling Light

- 13W 4000K/5600K LED ceiling light
- White painted metal base
- Opal acrylic diffuser with 3 twist lock clips
- Inbuilt integral driver
- Weather resistant IP44

* Compared to a standard T8 circular fluorescent lamp

PRODUCT SPECIFICATIONS

ELECTRICAL

Supply Voltage	230-240V AC
Supply Frequency	50-60Hz
Supply Current	100mA
Power Factor	0.92
Total Input Power	13W
Secondary Output Voltage	180V DC
Secondary Output Current	60mA
Lamp Power	13W

MATERIALS

Base	Metal
Diffuser	Acrylic
Diffuser Clips	Plastic
Lens	Polycarbonate
Controller Base & Cover	Thermoplastic

THERMAL

Ambient Temperature Rating	25°C
Maximum Surface Temp	65°C
Ingress Protection Rating	IP44

OPTICAL / PHOTOMETRIC

	4000K	5600K
Luminous Flux	610 lumens	800 lumens
CRI	>70	>70
Beam Angle	120°	120°

WEIGHT / LIFE

Weight	1.2Kg
LED Lamp Life	30,000HR



REFERENCE	COLOUR	CODE
XLLED116S	Opal	26560
XLLED116SD	Opal	27204

Panel & Systems

XL-LED PERFORMANCE