

XL-LED MINI PRO LED Gimbal Downlight Kits



Downlights

XL-LED PERFORMANCE

10000K
WARM

3000K
WARM

4000K
COOL


7000K
COOL

ENERGY SAVING
80%

LAMP LIFE
30,000

30% 100%
DIMMABLE

8W
614/710
LUMENS



KLEDO8WA



DIMENSIONS / WEIGHT / LIFE

Downlight	80g
LED Lamp Life	30,000HR
Controller Life	30,000HR

PRODUCT FEATURES



- XL-LED MINI PRO Gimbal Kit contents:
- 1 x 8W LED lamp (3000K or 4000K)
 - 1 x 12V, 650mA thermoplastic casing LED driver with click tooth cover prewired to 500mm lamp lead and 1.2m flex & plug
 - 1 x DL23LED gimbal downlight with twist-lock face
 - C-Bus compatible

* Compared to a standard MR16 50W lamp

PRODUCT SPECIFICATIONS

ELECTRICAL	
Supply Voltage	220-240V AC
Supply Frequency	50-60Hz
Supply Current	50mA
Power Factor	0.95
Total Input Power	9.8W
Secondary Output Voltage	12V DC
Secondary Output Current	650mA
Lamp Power	8W
Input Capacitance of Driver	0.047μF

MATERIALS	
Heatsink	Aluminium
Attachment Clip	Steel
Lens Retaining Clip	Steel, chrome plated
Lens	Polycarbonate
Controller Base & Cover	Thermoplastic
Body	Aluminium

THERMAL	
Thermal Protection	Overload, short-circuit
Ambient Temperature Rating	50°C
Maximum Surface Temp	75°C

	OPTICAL / PHOTOMETRIC	
	3000K	4000K
Luminous Flux	614 lumens	710 lumens
CRI	80	80
Beam Angle	45°	45°



REFERENCE	COLOUR	CODE
3000K		
KLEDO8WAW3K	White	27164
KLEDO8WASC3K	Satin Chrome	27165
4000K		
KLEDO8WAW4K	White	27166
KLEDO8WASC4K	Satin Chrome	27167