



**IMPORTANT:**  
**TURN OFF THE POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE STARTING INSTALLATION.**

**Carefully unpack and identify all parts before assembly. Bulbs are not included.**

1. Screw center pipe onto top of socket assembly while removing any slack in wires in between parts.
2. Install arms:
  - A. Install upper section of arms onto studs, which are located at top section of center pipe, by tightening set screw. Use enclosed hex key to tighten.
  - B. Install lower section of arms onto pan by fastening with machine screws.
3. Slide spacer tube till it sits on top of center pipe. Then screw upper font into center pipe while removing any slack in wire in between parts. Then screw fixture loop onto upper font.
4. Install a hex nut onto one end of long threaded pipe leaving about 1/2" (13 mm) thread exposed. Screw same end of threaded pipe into coupler. Tighten hex nut.
5. Slip glass shade up till it checks into bottom of pan. Then lock into position by fastening with flat washer and hex nut. Do not over tighten.
6. Slip lower font through same threaded pipe and lock into place by fastening finial.
7. Install light bulb (not included). See label located at socket area for type and maximum allowed wattage.
8. Install two glass plates onto top of socket assembly by placing holes in plates through four screw studs and securing with four ball cap nuts. Do not over tighten.
9. Follow enclosed **"Chain Suspended Fixture Installation Instructions"** for electrical and fixture installation onto ceiling outlet box.