

Series of recessed wall uplighters featuring a high purity aluminium reflector with faceted finish and anodised protection. The concealed light source and indirect illumination provide soft ambient lighting to any interior.

Control gear options for fluorescent lamps add suffix: -

- AD** Analogue dimming
- DSI** Digital dimming
- DALI** Addressable dimming

Note: Halogen lamp fittings may not be suitable for some types of wall finishes such as timber and paperlined plasterboard.




2774 KAYL ONE

240v 100W R7s 78mm

Recessed feature wall light with narrow aperture.

IP10




2776 KAYL TWO

240v 150W R7s 78mm

Recessed feature wall light with medium aperture.

IP10



2780 KAYL THREE

240v 200W R7s 118mm


Recessed feature wall light with wide aperture.

2788 KAYL THREE

240v 18W G24d-2

Recessed feature wall light with integral magnetic control gear.

IP10



2789 KAYL THREE

240v 18W G24d-2

Recessed wall light with opal acrylic diffuser. Acrylic diffuser only to be used for 18W compact fluorescent. Integral magnetic control gear.

IP40



01 10 28




2792 KAYL FOUR

240v 36W PL-L 2G11



Recessed feature light with wide aperture for energy saving fluorescent lamps. Integral non dimmable electronic HF control gear.

Dimmable version available on request

IP10



01 10



744 KAYL ONE
776 KAYL TWO
788 KAYL THREE
 Recessing box for cement rendered walls.

GAMMA ILLUMINATION

Head Office, 42-46 Scrivener St, Warwick Farm, NSW 2170, Australia
 Tel +61 2 9822 7333 Fax +61 2 9822 7399
 info@gammaillumination.com