




In-ground Uplighters Round



- In-ground uplighter round adjustable lamp (30°)
- Stainless steel 316 marine grade cover
- Flush tempered glass/Trafficable to 600kg
- Cut out not using plastic canister: 120mm
- Cut out using plastic canister: 124mm
- Face diameter: 129mm
- Installation depth: 145mm
- **NOTE: adequate drainage must be allowed**
- MR16 20w max
- IP rating: IP65
- Can be used with a halogen globe


IMAGE	PART NUMBER	COLOUR TEMP	OUTPUT	POWER	INCLUDED GLOBES
	HV1821C	Cool white, 6000k	300lm	12v LED 5w	5w LED globe
	HV1821W	Warm white, 3000k	250lm	12v LED 5w	5w LED globe

All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to pages (169 - 178)

All low voltage products that specify LED or are supplied with a 12v LED globe must be used with a suitable LED driver, refer to pages (188 - 192)



In-ground Uplighters Round



- In-ground uplighter round adjustable lamp (30°)
- Stainless steel 316 marine grade cover
- Flush tempered glass/Trafficable to 600kg
- Cut out not using plastic canister: 96mm
- Cut out using plastic canister: 104mm
- Face diameter: 120mm
- Installation depth: 125mm
- **NOTE: adequate drainage must be allowed**
- MR16 20w max
- IP rating: IP65
- Can be used with a halogen globe

IMAGE	PART NUMBER	COLOUR TEMP	OUTPUT	POWER	INCLUDED GLOBES
	HV1822C	Cool white, 6000k	300lm	12v LED 5w	5w LED globe
	HV1822W	Warm white, 3000k	250lm	12v LED 5w	5w LED globe

All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to pages (169 - 178)

All low voltage products that specify LED or are supplied with a 12v LED globe must be used with a suitable LED driver, refer to pages (188 - 192)