


Mini In-ground Uplighters Square

- In-ground uplighter square
- Stainless steel 316 marine grade cover
- Flush tempered glass
- Trafficable to 600kg
- Hole cut out not using plastic canister: 61mm
- Hole cut out using plastic canister: 64mm
- Installation depth needed: 98mm
- Face diameter: 70mm
- **NOTE: adequate drainage must be allowed**
- 12v MR11 20w max
- IP rating: IP65
- Can be used with a halogen globe

IMAGE	PART NUMBER	COLOUR TEMP	OUTPUT	POWER	INCLUDED GLOBES
	HV2701C	Cool white, 6000k	180lm	12v LED 2w	2w LED globe
	HV2701W	Warm white, 3000k	160lm	12v LED 2w	2w LED globe

All low voltage products that specify LED or are supplied with a 12v LED globe must be used with a suitable LED driver, refer to pages (188 - 192)



316 Stainless Steel Mini In-ground Uplighters Square

- In-ground uplighter square
- Full body stainless steel 316 marine grade
- Flush tempered glass/Trafficable to 600kg
- Hole cut out not using canister: 48mm
- Hole cut out using canister: 50mm
- Installation depth needed: 85mm
- Face diameter: 70mm
- **Cavity must be deep enough to allow for cabling**
- **Adequate drainage must be allowed**
- 12v MR11 20w max IP rating: IP65
- Can be used with a halogen globe

IMAGE	PART NUMBER	COLOUR TEMP	OUTPUT	POWER	INCLUDED GLOBES
	HV2705C	Cool white, 6000k	180lm	12v LED 2w	2w LED globe
	HV2705W	Warm white, 3000k	160lm	12v LED 2w	2w LED globe

All low voltage products that specify LED or are supplied with a 12v LED globe must be used with a suitable LED driver, refer to pages (188 - 192)