

## Highlite Aluminium Black

- LED Bollard light
- Aluminium Poly Powder Coated Black
- High grade perspex lens
- 600mm and 1000mm height
- Selectable wattage - 18w or 24w
- IP Rating: IP65
- IK Rating: IK08



HV1625T-BLK-240V  
HV1625T-BLK-24V



HV1626T-BLK-240V  
HV1626T-BLK-24V

IMAGE	PART NUMBER	COLOUR TEMP	LUMENS	INPUT	INCLUDED LED
	HV1625T-BLK-240V	3000K 4000K 5500K	1900lm 1970lm 2040lm	240v	<b>Tri-Colour</b> Built-in 24w SMD
	HV1625T-BLK-24V	3000K 4000K 5500K	1900lm 1970lm 2040lm	24v DC	<b>Tri-Colour</b> Built-in 24w SMD See page 276 for compatible drivers
	HV1626T-BLK-240V	3000K 4000K 5500K	1900lm 1970lm 2040lm	240v	<b>Tri-Colour</b> Built-in 24w SMD
	HV1626T-BLK-24V	3000K 4000K 5500K	1900lm 1970lm 2040lm	24v DC	<b>Tri-Colour</b> Built-in 24w SMD See page 276 for compatible drivers

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 275 - 282  
Lumen output measured at source. All globes supplied with fittings are non-dimmable. If you require 240v dimmable globes refer to page 362