

## TRIAC

- TRIAC Dimmable LED drivers
- Constant voltage 12v DC
- Must be installed with adequate ventilation
- Suits Havit 12v DC single coloured LED strip



### IP20 INDOOR

IMAGE	PART NUMBER	INPUT POWER	OUTPUT POWER	SIZE HxWxL (mm)
	<b>HV9660-12V30W</b>	240v AC	12v DC 30w	(H)20x (W)54x (L)155
	<b>HV9660-12V60W</b>	240v AC	12v DC 60w	(H)24x (W)61x (L)178

## TRIAC

- TRIAC Dimmable LED drivers
- Constant voltage 24V DC
- Must be installed with adequate ventilation
- Suits Havit 24v DC single coloured LED strip



### IP20 INDOOR

IMAGE	PART NUMBER	INPUT POWER	OUTPUT POWER	SIZE HxWxL (mm)
	<b>HV9660-24V30W</b>	240v AC	24v DC 30w	(H)20x (W)54x (L)155
	<b>HV9660-24V60W</b>	240v AC	24v DC 60w	(H)24x (W)61x (L)178



### IP66 WEATHERPROOF

IMAGE	PART NUMBER	INPUT POWER	OUTPUT POWER	SIZE HxWxL (mm)
	<b>HV9660-12V100W</b>	240v AC	12v DC 100w	(H)43x (W)70x (L)230
	<b>HV9660-12V150W</b>	240v AC	12v DC 150w	(H)47x (W)78x (L)265
	<b>HV9660-12V200W</b>	240v AC	12v DC 200w	(H)47x (W)78x (L)265
	<b>HV9660-12V300W</b>	240v AC	12v DC 300w	(H)47x (W)78x (L)278



### IP66 WEATHERPROOF

IMAGE	PART NUMBER	INPUT POWER	OUTPUT POWER	SIZE HxWxL (mm)
	<b>HV9660-24V100W</b>	240v AC	24v DC 100w	(H)43x (W)70x (L)230
	<b>HV9660-24V150W</b>	240v AC	24v DC 150w	(H)47x (W)78x (L)265
	<b>HV9660-24V200W</b>	240v AC	24v DC 200w	(H)47x (W)78x (L)265
	<b>HV9660-24V300W</b>	240v AC	24v DC 300w	(H)47x (W)78x (L)278

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274  
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336

All low voltage products that specify an input of 12v or 24v DC must be used with a suitable LED driver, refer to pages 267 - 274  
Lumen output measured at source. All globes supplied with fittings are non dimmable. If you require 240v dimmable globes refer to page 336