

HV1833W

240v LED 20w

In-ground uplighter round wide beam	
Stainless steel 316 marine grade cover	
Beam angle: 120°	
Flush tempered glass	Trafficable to 1000kg
Cut out not using plastic canister: 182mm	
Cut out using plastic canister: 194mm	
Face diameter: 213mm	Installation depth: 110mm
NOTE: adequate drainage must be allowed	
240v Built-in 20w LED	
Warm white, 3000k, 1600lm (HV1833W)	
IP Rating: IP67	

Built in COB 20w LED

HV1834W

240v LED 20w

In-ground uplighter round narrow beam	
Stainless steel 316 marine grade cover	
Beam angle: 60°	
Flush tempered glass	Trafficable to 1000kg
Cut out not using plastic canister: 182mm	
Cut out using plastic canister: 194mm	
Face diameter: 210mm	Installation depth: 270mm
NOTE: adequate drainage must be allowed	
240v Built-in 20w LED	
Warm white, 3000k, 2400lm (HV1834W)	
IP Rating: IP67	

Built in COB 20w LED

HV1835W

240v LED 30w

In-ground uplighter round	
Stainless steel 316 marine grade cover	
Beam angle: 120°	
Flush tempered glass	Trafficable to 1000kg
Cut out not using plastic canister: 220mm	
Cut out using plastic canister: 236mm	
Face diameter: 260mm	Installation depth: 125mm
NOTE: adequate drainage must be allowed	
240v Built-in 30w LED	
Warm white, 3000k, 2400lm (HV1835W)	
IP Rating: IP67	

Built in COB 30w LED

HV1833W
HV1834W
HV1835W

In-ground Uplighters Round

