


## HV1843W 12v LED 12w

- In-ground uplighter round
- Stainless steel 316 marine grade cover
- Beam angle: 60°
- Full stainless steel body
- Flush tempered glass
- Trafficable to 1000kg
- Cut out not using plastic canister: 166mm
- Cut out using plastic canister: 195mm
- Face diameter: 210mm
- Installation depth: 110mm
- NOTE: adequate drainage must be allowed
- 12v Built-in 12w LED
- Warm white, 3000k, 960lm (HV1843W)
- IP Rating: IP67
- Must be used with a suitable LED driver (Refer to Pages 173-184)

**Built in 12w LED**



HV1843W  
HV1845W

# In-ground Uplighters Round

## HV1845W 12v LED 18w

- In-ground uplighter round
- Stainless steel 316 marine grade cover
- Beam angle: 60°
- Full stainless steel body
- Flush tempered glass
- Trafficable to 1000kg
- Cut out not using plastic canister: 213mm
- Cut out using plastic canister: 237mm
- Face diameter: 250mm
- Installation depth: 118mm
- NOTE: adequate drainage must be allowed
- 12v Built-in 18w LED
- Warm white, 3000k, 1200lm (HV1845W)
- IP Rating: IP67
- Must be used with a suitable LED driver (Refer to Pages 173-184)

**Built in 18w LED**

