

# Mini In-ground Up-lighters



## HV2705C 12v LED 1.2w HV2705W

- In-ground uplighter square
- Full body stainless steel 316 marine grade
- Tempered glass
- Trafficable to 600kg
- Hole cut out not using canister: 48mm
- Hole cut out using canister: 50mm
- Installation depth needed: 85mm
- Face diameter: 70mm
- Adequate drainage must be allowed
- 12v MR11 20w max
- Cool white, 6000k, 90lm (HV2705C)
- Warm white, 3000k, 70lm (HV2705W)
- IP rating: IP65
- Can be used with a halogen globe
- Must be used with a suitable LED driver (Refer to Pages 153-158)

**Supplied with a replaceable 1.2w LED globe**



## HV2801C 12v LED 1.2w HV2801W

- In-ground uplighter round with eyelid (eyelid can be removed)
- Stainless steel 316 marine grade cover
- Flush tempered glass
- Trafficable to 600kg with eyelid removed
- Hole cut out not using plastic canister: 61mm
- Hole cut out using plastic canister: 64mm
- Installation depth needed: 98mm
- Face diameter: 70mm
- Adequate drainage must be allowed
- 12v MR11 20w max
- Cool white, 6000k, 90lm (HV2801C)
- Warm white, 3000k, 70lm (HV2801W)
- IP rating: IP65
- Can be used with a halogen globe
- Must be used with a suitable LED driver (Refer to Pages 153-158)

**Supplied with a replaceable 1.2w LED globe**

