

# Mini In-ground Up-lighters Round

<b>HV2802</b>	<b>240v LED 1.2w</b>
In-ground uplighter round with eyelid (Eyelid can be removed)	
Stainless steel 316 marine grade cover	
Flush tempered glass	
Trafficable to 600kg with eyelid removed	
Hole cut out not using plastic canister: 61mm	
Hole cut out using plastic canister: 64mm	
Installation depth needed: 98mm	
Face diameter: 70mm	
Adequate drainage must be allowed	
240v LEDx6 (1.2w total) with built in driver	
Cool white, 4000k, 90lm	
IP rating: IP65	
<b>Built in 6 chip 1.2w LED</b>	



<b>HV2805C</b>	<b>12v LED 1.2w</b>
<b>HV2805W</b>	
In-ground uplighter	
Full body stainless steel 316 marine grade	
Tempered glass	
Trafficable to 600kg	
Hole cut out not using canister: 48mm	
Hole cut out using canister: 50mm	
Installation depth needed: 85mm	
Face diameter: 70mm	
Cavity must be deep enough to allow for cabling	
Adequate drainage must be allowed	
12v MR11 20w max	
Cool white, 6000k, 90lm (HV2805C)	
Warm white, 3000k, 70lm (HV2805W)	
IP rating: IP65	
Can be used with a halogen globe	
Must be used with a suitable LED driver (Refer to Pages 153-158)	
<b>Supplied with a replaceable 1.2w LED globe</b>	

