

EM - E CEILING FAN



Antique brass motor with Walnut blades

Installation Locations:

Indoors

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan without light fittings attached:

Approximately 330mm

Motor:

16 Pole, 153mm x 18mm motor
Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Motor Housing:

Materials: Pressed Steel

Available Colours :

White, Brushed Chrome & Antique Brass

Blades:

Sizes: 38" (970mm)
Materials: NZ Plywood, Painted Finish
Blade Pitch: 12°

Available Colours:

White, Silver & Walnut

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Wall Controller Speed Capacitor Values:

3µF & 1.5µF

Rotational Diameter:

970mm (38") Straight Blade Sweep

Weight Including Packaging:

Complete fan: 7kg

Packaging Dimensions (cm):

Complete fan: 45L x 31W x 25H

Accessories:

Remote Control
Down Rod 26mm diameter
45° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses
Universal Mounting Brace

Warranty

2 years "in home" covering major defects
3 Years additional covering motor only (not labour)
Remotes -1 year "in home" covering major defects. (receiver and handpiece)
Lights -1 year "in home" covering major defects

Extra Information

Introduced into the HPI range in 2006
3 Speed wall controller
Light Adaptable
Reversible

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

	HIGH	MED	LOW
RPMS	240	191	124
WATTS	50.3	22	9.7
AIRFLOW[^]: AUS-ES / USA-ES	4569 / 6168	3622 / 4890	2634 / 3556
EFFICIENCY[^]: AUS-ES / USA-ES	90.83 / 122.63	164.64 / 222.26	271.55 / 366.59

[^] Airflow measured in Cubic metres/ Hour (CM/HR), Efficiency measured in CM/HR per watt (CMH/W)

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au