

MAJESTIC EVERGLADE CEILING FAN



Brushed Chrome with Broadleaf blades

Installation Locations:

Indoor & Outdoor (non-coastal, provided the fan is fully undercover) when assembled with broadleaf blades IP33 rated

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan:

Approximately 350mm

Motor:

16 Pole, 188mm x 20mm motor
Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Motor Housing:

Materials: Pressed Steel

Available Colours :

White, Brushed Chrome & Antique Brass

Blades:

Sizes: 1370mm (54")
Material: Bamboo blade, Plywood Timber
Broadleaf blade, PH475 plastic
Palm: Palm, Palm Leaf
Blade Pitch: 13°

Available Blade Colours:

Bamboo Style, natural & White; Broadleaf, Brown & White; & Palm

Extra Information:

Introduced into the HPI range in 2002
3 Speed Pull cord
Light Adaptable
Wall control does not come standard

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Wall Controller Speed Capacitor Values:

4.3µF & 2.1µF

Rotational Diameter:

1370mm (54") Blade Sweep

Weight Including Packaging:

Motor Unit: 8.9kgs
Blades: Bamboo: 1.6kgs
Broadleaf: 2.9kgs
Palm: 3.1kgs

Packaging Dimensions (cm):

Motor Unit: 38L x 31W x 31H
Blades: Bamboo: 58L x 23W x 7H
Broadleaf: 58L x 56W x 5H
Palm: 59L x 30W x 40H

Accessories:

Remote Control
Extension Down Rod 21mm diameter
45° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses
Universal Mounting Brace

Warranty

2 years "in home" covering major defects
3 Years additional covering motor only (not labour)
Remotes -1 year "in home" covering major defects.
(receiver and handpiece)
Lights -1 year "in home" covering major defects

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

<i>Figures shown are tested on Bamboo White Blades</i>	HIGH	MED	LOW
RPMS	172	116	69
WATTS	81.8	39.1	15.2
AIRFLOW[^]: AUS-ES / USA-ES	10542 / 14232	6991 / 9438	4111 / 5550
EFFICIENCY[^]: AUS-ES / USA-ES	128.88 / 173.99	178.80 / 241.38	270.46 / 365.12


[^] Airflow measured in Cubic metres/ Hour (CM/HR), Efficiency measured in CM/HR per watt (CMHW)

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au

MAJESTIC RANGE CEILING FAN LIGHTING



78mm Halogen Light (MAX 100W)




- Cost effective
- Colour—warm white
- Dimmable
- Compact in size



78mm linear Halogen Light globe

E27 Light (MAX 2x40W)



- Accepts a variety of lamps, e.g. incandescent, fluorescent.
- Cost effective
- Compatible with some CFL lamps



E27

GLACIER STYLE GLASS





ECLIPSE STYLE GLASS



Colours Available:

All light kits are available in most motor colours ~ White, White Birch, Black, Brushed Chrome, Polished Brass, Antique Brass, Burnt Copper and Stainless Steel.

GX53M 14W Compact Fluorescent Light



- A Base
- B Lamp Assembly
- C Tube

- Low wattage
- High light output
- Liquid mercury free
- Colour—Warm white/Cool white colour temperatures available
- Low heat
- 12000 hour life span
- 2700k or 3000k


Packaging Dimensions

17H x 25W x 25L

Weight

1.5 kg

Flat 6, 26W Fluorescent Lamp



- High Efficiency (EEL=A2)
- High light output
- Liquid mercury free
- Low heat
- Fewer shadows visible
- Dimmable on certain fan models; ecO² & Ice Range (with Model 089 FLDR)
- 4100k

^ All light kits must be installed by a licensed electrician. For further information about correct installation procedures, please see www.hunterpacific.com.au

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au