

KINETIC CEILING FAN



Polished Aluminium

Installation Locations:

Indoor and outdoor (provided the fan is fully undercover)

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan:

Approximately 370mm

Motor:

16 Pole, 153mm x 18mm motor
Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Motor Housing:

Materials: Die Cast Aluminium

Available Colours :

White, White Birch, Matt Black, Polished Aluminium & Brushed Aluminium

Light Adaptable - Available Light Assembly Kits

Kinetic Light Assembly available in; 78mm 100w Linear Halogen, E14 Light (MAX 2x40W), 14W GX53M, Flat 6 26W Fluorescent Lamp. *Light insert only is required*

Blades:

Sizes:1320mm (52") timber blade
Materials: NZ plywood, Painted finish
Blade Pitch: 12°

Available Blade Colours:

White, White Birch, Matt Black, Polished Aluminium & Brushed Silver

Extra Information:

Introduced into the HPI range in 2008
3 speed wall controller
Reversible
Light Adaptable

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Wall Controller Speed Capacitor Values:

3µF & 2µF

Rotational Diameter:

1320mm (52) Blade Sweep

Weight Including Packaging:

Complete fan: 10.5kg
Light Fitting: 0.26kg

Packaging Dimensions (cm):

Complete Fan: 63L x 37W x 40H

Accessories:

Remote Control
Extension Down Rod 26mm diameter
45° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses
Universal Mounting Brace

Warranty

2 years "in home" covering major defects
3 Years additional covering motor only (not labour)
Remotes -1 year "in home" covering major defects. (receiver and handpiece)
Lights -1 year "in home" covering major defects

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised For USA Energy Star compliance.

	HIGH	MED	LOW
RPMS	200	139	102
WATTS	64.7	28.6	16.6
AIRFLOW[^]: AUS-ES / USA-ES	8953 / 12087	5764 / 7781	4341 / 5860
EFFICIENCY[^]: AUS-ES / USA-ES	138.38 / 186.81	201.54 / 272.08	261.51 / 353.03

[^] Airflow measured in Cubic metres/ Hour (CM/HR), Efficiency measured in CM/HR per watt (CMH/W)

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au