

TYPHOON MOULDED CEILING FAN



Brushed Chrome with silver blades

Installation Locations:

Indoor Only

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan:

Approximately 350mm

Motor:

16 Pole, 188mm x 15mm motor
Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Motor Housing:

Materials: Pressed Steel (Painted, Plated or Powder Coated Finish)

Available Colours :

White, Brushed Chrome & Stainless Steel

Blades:

Sizes:1320mm (52")
Materials: Injection Moulded Plastic
Blade Pitch: 23°

Available Blade Colours:

White, Clear & Silver

Extra Information:

Introduced into the HPI range in 2009
3 Speed wall controller
Light Adaptable
Reversible
Low maintenance and safe moulded blades

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Wall Controller Speed Capacitor Values:

3.5µF & 1.7µF

Rotational Diameter:

1320mm (52") Blade Sweep

Ceiling to top side of the blade:

265mm

Weight Including Packaging:

Complete fan 1320mm (52") : 8.1kg

Packaging Dimensions (cm):

Complete fan 1320mm (52"): 62L x 22W x 27H

Accessories:

Remote Control
Extension Down Rod 21mm diameter
45° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses
Universal Mounting Brace

Warranty

2 years "in home" covering major defects
3 Years additional covering motor only (not labour)
Remotes -1 year "in home" covering major defects.
(receiver and handpiece)
Lights -1 year "in home" covering major defects

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised For USA Energy Star compliance.

<i>Figures shown are tested on 52" Fan</i>	HIGH	MED	LOW
RPMS	231	149	70
WATTS	71.5	34.6	10.7
AIRFLOW[^]: AUS-ES / USA-ES	11576 / 15628	7482 / 10101	3361 / 4537
EFFICIENCY[^]: AUS-ES / USA-ES	161.90 / 218.57	216.24 / 291.93	314.11 / 424.05

[^] Airflow measured in Cubic metres/ Hour (CM/HR), Efficiency measured in CM/HR per watt (CMH/W)

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au

TYPHOON 316 MOULDED CEILING FAN



Brushed Chrome with silver blades

Installation Locations:

Indoor, outdoor and Coastal areas (provided the fan is fully undercover)

Recommended Height:

There should be at least 2.1m between the lowest point of the fan blades and the floor.

Top of canopy cover to lowest point of the fan:

Approximately 350mm

Motor:

16 Pole, 188mm x 15mm motor
Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

Motor Housing:

Materials: Marine Grade 316L Stainless Steel

Available Colours :

Stainless Steel (Natural Grain)

Blades:

Sizes:1320mm (52")
Materials: Injection Moulded Plastic
Blade Pitch: 23°

Available Blade Colours:

Clear & Silver

Extra Information:

Introduced into the HPI range in 2009
3 Speed wall controller
Light Adaptable
Reversible
Low maintenance and safe moulded blades

Standard Canopy Cover:

Suitable for flat and pitched ceilings up to 28°

Wall Controller Speed Capacitor Values:

3.5µF & 1.7µF

Rotational Diameter:

1320mm (52") Blade Sweep

Ceiling to top side of the blade:

265mm

Weight Including Packaging:

Complete fan 1320mm (52") : 8.1kg

Packaging Dimensions (cm):

Complete fan 1320mm (52"): 62L x 22W x 27H

Accessories:

Remote Control
Extension Down Rod 21mm diameter
45° Ceiling Kit (for pitched ceilings)
T-Hook for ceiling roses
Universal Mounting Brace

Warranty

2 years "in home" covering major defects
3 Years additional covering motor only (not labour)
Remotes -1 year "in home" covering major defects. (receiver and handpiece)
Lights -1 year "in home" covering major defects

Airflow and Efficiency:

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised For USA Energy Star compliance.

<i>Figures shown are tested on 52" Fan</i>	HIGH	MED	LOW
RPMS	231	149	70
WATTS	71.5	34.6	10.7
AIRFLOW[^]: AUS-ES / USA-ES	11576 / 15628	7482 / 10101	3361 / 4537
EFFICIENCY[^]: AUS-ES / USA-ES	161.90 / 218.57	216.24 / 291.93	314.11 / 424.05


[^] Airflow measured in Cubic metres/ Hour (CM/HR), Efficiency measured in CM/HR per watt (CMH/W)

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au

TYPHOON RANGE CEILING FAN LIGHTING



78mm Halogen Light (MAX 100W)




- Cost effective
- Colour—warm white
- Dimmable
- Compact in size



78mm linear Halogen Light globe

E27 Light (MAX 2x40W)



- Accepts a variety of lamps, e.g. incandescent, fluorescent.
- Cost effective
- Compatible with some CFL lamps



GLACIER STYLE GLASS





ECLIPSE STYLE GLASS



Colours Available:

All light kits are available in most motor colours ~ White, White Birch, Black, Brushed Chrome, Polished Brass, Antique Brass, Burnt Copper and Stainless Steel.

GX53M 14W Compact Fluorescent Light



- A Base
- B Lamp Assembly
- C Tube

- Low wattage
- High light output
- Liquid mercury free
- Colour—Warm white/Cool white colour temperatures available
- Low heat
- 12000 hour life span
- 2700k or 3000k


Packaging Dimensions

17H x 25W x 25L

Weight

1.5 kg

Flat 6, 26W Fluorescent Lamp



- High Efficiency (EEL=A2)
- High light output
- Liquid mercury free
- Low heat
- Fewer shadows visible
- Dimmable on certain fan models; ecO² & Ice Range (with Model 089 FLDR)
- 4100k

^ All light kits must be installed by a licensed electrician. For further information about correct installation procedures, please see www.hunterpacific.com.au

For full warranty details please see Hunter Pacific International's website www.hunterpacific.com.au