

Landscape Lighting

LED Globes

Warm White	2700K
Cool White	5700K
Red	627nm typ.
Green	530nm typ.
Blue	470nm typ.
Amber	590nm typ.


Aqualux has developed a range of LED drop-in globes that are designed especially for Landscape Lighting. Useful in a wide variety of applications, the 4W range is perfect for both retro-fitting of old luminaires as well as new installations.

True MR16 GX5.3 Form → Fits all MR16 / GX5.3 Luminaires.

4W Mid-Power LED Technology → Thermally optimised for enclosed fittings.

3000K / 5000K / Amber / Red / Green / Blue → Lighting design flexibility.

12 ~ 24V AC/DC MultiVoltage™ Compatible → Voltage drop compensating.



Technical

	Warm White	Warm White GU10	Cool White	Amber	Red	Green	Blue
POWER	4W	4W	4W	4W	4W	4W	4W
OUTPUT	250lms	250lms	260lms	-	-	-	-
EFFICACY	62.5lm / W	62.5lm / W	65lm / W	-	-	-	-
CCT	3000K	3000K	5000K	592 nm typ.	627 nm typ.	530nm typ.	470nm typ.
CRI	83 (Ra)	83 (Ra)	83 (Ra)	-	-	-	-
LED	SSC 3030	SSC 3030	SSC 3030	Luxeon Z	Luxeon Z	Luxeon Z	Luxeon Z
BEAM ANGLE	35 Degrees	35 Degrees	35 Degrees	35 Degrees	35 Degrees	35 Degrees	35 Degrees
LIFETIME	30,000 Hours	30,000 Hours	30,000 Hours	30,000 Hours	30,000 Hours	30,000 Hours	30,000 Hours
VOLTAGE	12V ~ 24V AC / DC	240 VAC	12V ~ 24V AC / DC	12V ~ 24V AC / DC	12V ~ 24V AC / DC	12V ~ 24V AC / DC	12V ~ 24V AC / DC
BASE	GX5.3	GU 10	GX5.3	GX5.3	GX5.3	GX5.3	GX5.3
DIMENSIONS	50mm D x 46mm H	50mm D x 60mm H	50mm D x 46mm H	50mm D x 46mm H	50mm D x 46mm H	50mm D x 46mm H	50mm D x 46mm H
PART CODE	AGL-MR16-LED-4W-WW	AGL-GU10-LED-4W-WW	AGL-MR16-LED-4W-CW	AGL-MR16-LED-4W-AY	AGL-MR16-LED-4W-AY	AGL-MR16-LED-4W-AY	AGL-MR16-LED-4W-AY

