



BARGO SE7355L/TC - 14W

LED 14 watt surface mount, rectangular profile wall luminaire with selectable CCT

Application

Residential walkways, exterior facades, interior commercial features

Design Specifications

- Durable aluminium body profile
- Matt black powder coat finish (RAL9005)
- High efficiency LED optics, opal polycarbonate diffuser
- Selectable CCT 3000/4000/6000K
- Beam distribution 160°
- Integral flickerCONTROLLED 14 watt control gear, IK06, IP54 performance

Performance

- Dimmable - NO



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7355LTC	240	14	900/1000/950	3000/4000/6000	80
Beam Angle (°)	Mass (kg)	Dim (mm)		Body Colour		
160	1.67	135(L) x 120(W) x 260(H)		BLACK		

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions

