



BONDI SE7124TC - 2 x 4W

IP65 LED architectural twin spot wall luminaire

Application

A decorative residential or commercial, exterior or interior LED solution

Design Specifications

- Choice of a cast aluminium body with a black or white powder coat or aluminium stainless finish
- Clear tempered glass cover
- High efficiency LED optics, beam distribution 50°
- 2 x 4 watt TC selectable GU10 lamps included
- Adjustable (downward) optical heads
- **Sensor options available**

Performance

- Dimmable - **NO**



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7124TC/BK	240	8	360/400/380	3000/4000/6000	80
	SE7124TC/WH	240	8	360/400/380	3000/4000/6000	80
	SE7124TC/AST	240	8	360/400/380	3000/4000/6000	80

Beam Angle (°)	Mass (kg)	Diameter (mm)	Dim (mm)	Body Colour
50	0.68	60	100(W) x 110(H)	BLACK
50	0.68	60	100(W) x 110(H)	WHITE
50	0.68	60	100(W) x 110(H)	ALUMINIUM STAINLESS



Note: lumens (lm) displayed are per optical head, power (W) is total load

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

