



DICE II S9016/2 - 16W

Surface mount rectangular, dimmable LED downlight, CRI > 90

Application

Ideal for any residential or commercial interior space

Design Specifications

- Surface mounted architectural style, rectangular profile downlight
- Centre tilt 30 degree at each head
- Durable die-cast aluminium body profile, black finish as standard, white optional
- High output (CRI>90) COB LED chip, polycarbonate optical lens, integral constant current trailing edge dimmable LED driver
- Changeable multi-faceted reflector system

Performance

Dimmable - **YES**

Dimmer Type - **Trailing edge**



Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	Beam Angle (°)	Dimmable
S9016/2WW/BK	240	16	1240	3000	60	YES

Technical Specification

Model No.	CRI	Body Colour	Dim (mm)
S9016/2WW/BK	90	BLACK	196(L) x 100(W) x 100(H)

Note: Lumens (lm) and Power (W) values shown are TOTAL system

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".



Dimensions



Dimensions

