



FLEXI 12V LV SINGLE COLOUR IP44, FL1206/S-6W/M

Run length 5 metre, IP44, LED single coloured strips

Application

Versatile single coloured IP44 LED strips

Design Specifications

- High efficiency SMD LED chips with 3M self adhesive tape
- Maximum run per driver 5m, cuttable every 50mm
- Connection length can be extended by certain LED driver, controllers and repeaters
- Heat sink and 12V constant voltage driver required
- Dimming options: (refer category introduction)
Type A - Trailing edge dimming,
Type B - LED strip controller LT8915DIM/BT with LT8914DIM/RP if required,
Type C - Analogue 1-10V
- LED channel options refer this section



-
-
-
-
-
-

Performance

Dimmable - **OPTIONAL**

Dimmer Type - **refer dimming options**

Technical Specification

Model No.	Input Voltage (V/DC)	Watts per metre (W/m)	Beam Angle (°)	Luminous Flux Per Meter (lm/m)	LEDs Per Metre	Dim (mm)
FL1206RD/S	12	6	115	120	60	10(W) x 3.5(H)
FL1206GN/S	12	6	115	220	60	10(W) x 3.5(H)
FL1206BU/S	12	6	115	60	60	10(W) x 3.5(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Product Images

