



LED STD25EM - 18/36W

Wide body LED 18-36 watt surface mount diffused linear batten

Application

Conventional linear LED batten profile ideal for residential and commercial spaces

Design Specifications

- Durable metal body profile, white powder coat finish
- High efficiency LED T8 tubes fitted, choice of 3000K, 4000K, 6000K, CRI>80
- Large terminal block, easy installation, safety fuse included
- High performance PMMA prism diffuser, beam distribution 120 degree
- Non maintained, independent emergency end cap, emergency with LiFePO4 battery included compliant to AS/NZS2293
- LED charge status display and test switch, guaranteed 90 minutes emergency function



Technical Specification

Model No.	Description	Input Voltage (V/AC)	Power (W)	CRI	Beam Angle (°)	Body Colour
STD25/206 EM	LED DIFFUSED BATTEN 2 X 9W EM	240	18	80	120	WHITE
STD25/212EM	LED DIFFUSED BATTEN 2 X 18W EM	240	36	80	120	WHITE

Technical Specification

Model No.	Dim (mm)
STD25/206 EM	630(L) x 109(W) x 83(H)
STD25/212EM	1260(L) x 109(W) x 83(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Product Images

